



12 Block – Thickness 12

Technical characteristics

The 12 cm block fulfils all interior insulation needs for renovations of old buildings. It regulates humidity naturally, which allows it to be used to insulate interior and exterior walls that are more humid. This block offers good thermal phase-shift, regulates heat, and improves living comfort significantly. Its thickness also allows it to be used in interior masonry. This block also offers very good sound insulation. From this thickness, hemp blocks are an efficient solution for exterior insulation of buildings.

	Value	Unit	Standard
Thickness	12	cm	
Modular dimensions	60 x 30	cm	
Number of blocks per m ²	5,5	blocks/m ²	
Maximum block weight	9,9	kg	
Weight of the masonry	0,60	kN/m ²	
Adhesive consumption	4,7	kg/m ²	
Dry thermal resistance	1,79	m ² K/W	EN 12667
Thermal resistance at 50% RH	1,69	m ² K/W	EN 12667
Phase shift λ	0,071	W/mK	EN 12667
Phase shift	7,9	h	ISO 13786
Sound reduction index* Rw	38 (-1;-3)	dB	ISO 10140-2
Acoustic absorption coefficient α	0,85		EN ISO 354 : 2003
Equivalent air layer thickness Sd	0,34	m	EN ISO 12572
Water vapour resistance factor μ	2,8		EN ISO 12572
Compressive strength	0,22	MPa	EN 772-1
Reaction to fire	B, s1, d0		NF EN 13501-1
Compressive strenght at ULS fd	0,099	MPa	
Resistance to fire with render	EI 45	min	EN 1364-1

* Coated hempblok 15mm on one side – Simulated value

** Hemp block masonry plastered on the fire side

Advantages

- Natural humidity control
- Thermal inertia input
- Quick and easy implementation
- Significant thermal phase-shift

Packaging

	Value	Unit
Dimensions of a pallet	120 x 100 x 122	cm
Maximum weight of a pallet	560	kg
Number of blocks per pallet	54	blocks/pallet
Number of m ² per pallet	9,72	m ² /pallet
Number of blocks per m ²	5,5	blocks/m ²

Storage

Pallet with shelf stored outside	6 months
Open pallet and exterior wall in progress	3 months
Masonry under completed roof	1 year with a maximum of 1 winter

Applications

-  Interior insulation
-  Exterior insulation
-  Interior walls