

Clay base

Technical characteristics

ClayWall clay rendering is the ideal environmentally friendly solution.

It's 100% natural and has many advantages that greatly enhance the living comfort of your home. Made from raw clay and natural pigments, it's a local material of exceptional quality. It's available in many shades and gives you a durable, matte, and modern finish.

	Clay Base	Clay Finish		
Apparent density	1600 k	1600 kg/m³		
Laying thickness	max 30 mm	4 - 6 mm		
Consumption	16kg/m²/cm			
Operating time	Several days of use			
Limit of use	5 to 30 degrees			

To guarantee the watertightness of a wall, a minimum thickness of 3 cm is needed.

Advantages

- Easy to implement
- Permeable to water vapour
- Acoustic comfort
- 100% natural product

Packaging

	Bags	BigBag	
Dimensions of a pallet	120 x 100 x 90	80 x 120 x 95	
Maximum weight of a pallet	1000kg	1200kg	
Number of bags per pallet	50 bags	1 Big Bag	
Bag weight	20kg		
Storage	Dry and away from moisture		
Storage life	3 months		





ARGF - ARGFS

Coatings and finishes

Clay finish

	Α	В	С	D
1				
2				
3				
4				
5				
6				
7				
8				
9				
10		L L		

